

SPECIALTY MEMBRANES

PEEL & STICK TPO MEMBRANE

Genflex

GenFlex TPO Peel and Stick Membrane is .045" reinforced TPO membrane with 8 mils of preapplied pressure sensitive adhesive. Peel & Stick Membrane rolls are 37.5" x 100'. TPO Membrane can be used in conjunction with all GenFlex TPO membrane systems.

ITEM # 757072 37 1/2" X 100'



TW-60 MOISTURE WRAP MEMBRANE 36" X 67' (2 SQ ROLL)

Tamko

TAMKO® TW-60 is a flexible, self-adhering rubberized asphalt sheet waterproofing membrane with a heavy polyester film on the surface, and a removable silicone release film on the adhesive side.

TAMKO TW-60 is especially well suited for below-grade waterproofing of foundation walls, tunnels, earth shelters, and similar structures. The TW-60 membrane is also suitable for waterproofing plaza decks, parking decks, balconies, and terraces.

ITEM # 752115

ADHESIVES, PRIMERS AND TAPES

ETERNABOND

ETERNABOND ETERNA-PRIME

Eternabond

Primer developed for eternabond tapes.

ITEM # 753610 QUART TUBES



ETERNABOND ROOF-SEAL

Eternabond

Eternabond RoofSeal (Gray/Black)

RoofSeal is the best solution for leak repair or corrosion protection in tough environments and conditions, including land-fill and pond liners. Our specialized backing has proven to be UV stable, even after 16 years in full sunlight. Our patented adhesive has an integrated primer which allows RoofSeal to BOND with the surface it is installed on. Perfect for reseaming all roofs, regardless of the material. Rubber, fiberglass, aluminum, modified, shingle, PVC, steel, hot-tar, etc., RoofSeal makes a permanent water-tight seal. Elongation factor greater than 700% guarantees RoofSeal will flex, expand and contract in all conditions, even on liners! Can be installed to -20 degrees F (with our EternaPrime). Sag rating of over 250 degrees F. 10 year warranty. Also great for tank repairs. (Formerly MP-Seal)

ITEM	# 753615	6" X 50' BLACK	35 MIL
	# 753616	4" X 50' BLACK	35 MIL
	# 753618	12" X 50' BLACK	35 MIL
	# 753622	4" X 50' WHITE	35 MIL
	# 753625	6" X 50' WHITE	35 MIL



ETERNABOND 6" WEBSEAL

Eternabond

WebSeal is 30 mils thick and is available in rolls 50' long, 4" wide. WebSeal has a woven backing laminated to our industrial adhesive tape. Easy to work with and extremely flexible, WebSeal forms around almost anything from a seam or tear to a leaking drain pipe. Once on it stays flexible but never loses its adhesion if properly applied. When used in a place exposed to sunlight, WebSeal is easily protected from UV rays using our flexible drying U.V. Protector, which brushes on easily and is included in all our product kits and can be tinted to match almost any color. Economical and easy to use, WebSeal continues to be the product of choice for repairing or reseaming RV and mobile home roofs, steel roofs, and more!

ITEM # 753630

ROOFING PRODUCTS

www.stetsonbuildingproducts.com



ETERNABOND DOUBLESTICK

Eternabond

Utilizing our aggressive sealing adhesive, DoubleStick is sticky on both sides and is perfect for use as a gasket when installing windows, vents, etc. on RVs, mobile homes, steel buildings. Once DoubleStick is applied, you can virtually forget about leaks! In addition, DoubleStick can be folded or rolled into a bead for areas that need a thicker gasket. DoubleStick comes in standard rolls 60 mils thick, 50' long, and 2" wide, and can be special-ordered in 4" and 6" wide rolls.

ITEM # 753640 2" X 50' 60 MIL



MATRIX SELECT SBS ADHESIVE

GAF Materials

MATRIX™ 102 SBS Adhesive is a select, asbestos-free formulation for use as a cold-applied bonding agent for SBS modified bitumen base sheets and SBS modified bitumen roof membranes. In addition, the formulation is non-destructive to asphalt based roofing membranes. Though combustible, this product requires no "red tag" labeling for fire hazard. Uses MATRIX™ 102 SBS Adhesive is designed to apply SBS modified bitumen base sheets and SBS modified bitumen roof membranes to approved substrates, such as structural concrete roof decks, existing smooth surface asphalt built-up roofs, polyisocyanurate insulation, Type G2 base sheets or other approved surfaces. Do not use with any APP modified products.

ITEM # 753048 #102, 5 GL PAIL



TPO SEAM TAPE

Genflex

GenFlex TPO White 3" Seam Tape is an extruded white rubber tape adhesive designed to provide a high strength, watertight seam in TPO roofing membranes. GenFlex Seam Tape is soft and tacky for quick grab to TPO and provides high initial strength at 70°C (158°F). The 3" tape is available in 100' lengths and comes pre-applied to silicone treated release liner.

ITEM # 757088 3" X 100' WHITE

Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



EPDM SEAM TAPE

Genflex

GenFlex Seam Tape is an extruded black rubber tape adhesive designed to provide a high strength, watertight joint in single-ply roofing membrane. GenFlex Seam Tape is soft and tacky for quick grab to EPDM, yet possesses high initial strength at 70°C (158°F). The tape is wound in rolls on a release liner.

ITEM	# 757089	3" X 100'	BLACK
	# 757090	7" X 100'	BLACK



BAR ANCHOR COVER TAPE

Genflex

GenFlex Cover Tape is an extruded black rubber tape adhesive that is laminated to cured EPDM rubber strips. GenFlex Cover Tape is designed to provide a high strength, watertight seal over GenFlex Anchor Bars on all GenFlex Roofing Systems mechanically attached EPDM systems.

GenFlex Cover Tape may be used GenFlex Cover Tape may be used to strip in metal flanges on some GenFlex TPO systems.

ITEM	# 757091	5" X 100'
	# 757092	12" X 100'



TERMINATION CAULK

Genflex

GenFlex Termination Caulk is a one-part polyurethane sealant that is used as a sealing agent on termination bars and fasteners at parapet walls and other termination points.

GenFlex Termination Caulk may be used for EPDM, RM, and TPO systems. This is NOT intended to be used as a seam sealant.

ITEM	# 757096	TUBE
------	----------	------



EDGE CAULK

Genflex

GenFlex Edge Caulk is a one-part elastomeric sealant that is used primarily with the Cover Tape.

It offers excellent adhesion to EPDM and other surfaces.

ITEM	# 757097	BLACK	TUBE
	# 757098	BLACK	5 GAL. PAIL

Omaha, NE (800) 383-1272 • Rockford, IL (800) 383-3808
Rock Island, IL (800) 383-1240 • Waterloo, IA (800) 383-2959

ROOFING PRODUCTS

www.stetsonbuildingproducts.com

WATERSTOP

Genflex

Waterstop is a one-component, low viscosity, self wetting, butyl blend mastic designed to be used in conjunction with roofing systems. It is primarily used as a sealing agent between the GenFlex membranes and applicable when the membrane is being terminated using a compression type seal.

Waterstop is an extremely tacky material and will remain as such when used with compression type terminations.

ITEM # 757099 TUBE



PRIMER

Genflex

GenFlex Primer is an adhesion promoter that must be used to prior to applying any GenFlex peel and stick accessory to GenFlex EPDM Systems.

ITEM # 757125 1 GAL. PAIL
757126 5 GAL. PAIL



BONDING ADHESIVE

Genflex

GenFlex EPDM Bonding Adhesive is a water based latex, low VOC contact adhesive designed to attach GenFlex EPDM membrane to High Density Wood Fiberboard, Polyisocyanurate, or other approved substrates.

The low VOC provides a product that conforms to many air quality requirements. This product may be substituted for the solvent based bonding adhesive.

ITEM # 757127 5 GAL. PAIL



G-400 SPLICE ADHESIVE

Genflex

GenFlex G-400 Splice Adhesive may be used to seam GenFlex EPDM sheets in Fully Adhered, Mechanically Attached, and Ballasted systems. GenFlex G-400 Splice Adhesive has excellent adhesion to EPDM and has excellent initial strength at 70°C (158°F).

ITEM	# 757128	1 GALLON
	# 757129	5 GALLON



RM BONDING ADHESIVE TYPE "S" #060060

Genflex

GenFlex RM Bonding Adhesive is a solvent-based adhesive used to adhere GenFlex RM and GenFlex RM-T to various substrates, including polyisocyanurate and wood fiberboard insulations.

ITEM	# 757337	5 GAL.	PAIL
------	----------	--------	------

CLEAR PRIMER (TPO) #30025

Genflex

GenFlex Clear Primer is an adhesion promoter that must be used prior to applying any GenFlex peel and stick accessory to GenFlex TPO systems.

ITEM	# 757422	3 GAL.	PAIL
------	----------	--------	------



TPO EDGE SEALANT

Genflex

GenFlex TPO Edge sealant is a one-part liquid elastomeric sealant that is used primarily as a sealing agent on cut edges of the TPO membrane after they are heat welded. It offers good adhesion to TPO membrane and other surfaces.

ITEM	# 757428	WHITE	#030420	16 OZ. BOTTLE
	# 757520	GREY	#30211	16 OZ. BOTTLE



TPO EDGE CAULK #30023

Genflex

Used for sealing edges of TPO roofing membrane.

ITEM	# 757429	WHITE	TUBE
------	----------	-------	------

ROOFING PRODUCTS

www.stetsonbuildingproducts.com

TPO COVER TAPE KIT

Genflex

GenFlex White TPO Cover Tape consists of a white tape adhesive that is laminated to a white thermoplastic cover strip. GenFlex White Cover Tape may be used to strip in metal flanges on GenFlex TPO systems. Packaged with the White TPO Cover Tape is a tube of GenFlex Edge Caulk (White) and scrub pads and handle.

ITEM	# 757457	5"X100'	WHITE
	# 757522	5" X 100'	GREY



#19 FLASHING CEMENT

Karnak

Karnak #19 Flashing Cement is a general purpose cement for repairing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, downspouts, and cornices. Application by trowel provides a durable, elastic coating of excellent adhesion and high resistance to water and weathering.

ITEM	# 756011	3 GAL.	PAIL	ULTRA WINTER GRADE
------	----------	--------	------	--------------------

#19AF (ASBESTOS FREE) SUMMER GRADE FLASHING CEMENT

Karnak

Karnak #19AF Flashing Cement is a general purpose cement for repairing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, downspouts, and cornices. Application by trowel provides a durable, elastic coating of excellent adhesion and high resistance to water and weathering.

ITEM	# 756014	3 GAL.	PAIL	
	# 756020	3 GAL.	PAIL	ULTRA SUMMER GRADE



#66AF ASBESTOS FREE BRUSH GRADE FLASHING CEMENT

Karnak

Karnak #66AF Modified Bitumen Adhesive is a cold-applied, SBS polymer modified asphalt adhesive, that provides great adhesion and elongation properties.

ITEM	# 756030	5 GAL.	PAIL	
------	----------	--------	------	--

Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



#155AF ASBESTOS FREE AMPHIBIKOTE

Karnak

Karnak #155AF Amphibikote is carefully prepared, emergency roof cement with special water displacing characteristics, which ensures an effective bond to both wet and dry surfaces. The #155AF is a cold process, heavy bodied, trowel applied roof cement ideal for repairing leaks in asphalt built-up roofs, flashing on walls, chimneys, skylights and vents, down-spouts, and gutters.

ITEM	# 756031	SUMMER GRADE	3 GAL.
	# 756032	WINTER GRADE	3 GAL.



MILLENNIUM WEATHERTIGHT POURBLE FOAM INSULATION ADHESIVE

Millennium Adhesive Products

Weather-Tite Pourable Foam Insulation Adhesive is a single component, elastomeric, low rise urethane foam adhesive that contains no solvents and does not require special tools or applicators. This liquid applied adhesive will, within minutes after application, begin to set, transforming into a strong low rise foam.

ITEM	# 757700	3 GAL.	PAIL
------	----------	--------	------




Q-15 ELASTOMERIC FLASHING CEMENT (WINTER)

Tamko

A heavy-bodied wet/dry formula rubberized mastic cement that is specially designed to remain pliable without running. Blended from durable roofing asphalt, select petroleum solvents and tough interlocking fibers for vital thixotropic properties. 100% ASBESTOS FREE. Available in winter or summer grades.

Ideal for use on vertical and horizontal asphalt roofing flashing systems and waterproofing detail work, such as parapets and drains.

ITEM	# 752401	5 GAL.	PAIL
------	----------	--------	------



TWP-2 WATER BASED PRIMER

Tamko

TAMKO TWP-2 is a high-quality rubberized water-based primer formulated for the professional waterproofing contractor. Provides maximum bond to asphalt, concrete, masonry, and metal surfaces. Ideal for use in preparing surfaces to receive TAMKO TW-60 Sheet Waterproofing Membranes.

ITEM	# 752515	5 GAL.	PAIL
------	----------	--------	------