



.060 EPDM FLASHING FLEX FLASH E

Genflex

Uncure EPDM may be used to flash corners and pipes in accordance to Genflex specifications.

ITEM	# 757080	6" X 100' ROLL
	# 757081	9" X 100' ROLL
	# 757082	12" X 100' ROLL
	# 757083	18" X 100' ROLL



7" PEEL & STICK FLASHING GENFLEX

Genflex

GenFlex Peel and Stick Flashing is composed of uncured EPDM laminated to a cured EPDM based adhesive tape. GenFlex Peel and Stick Flashing is specifically designed to be used in roofing applications for flashing of pipes, inside corners, outside corners, perimeter edge metal, wall base termination cover, and any application for uncured EPDM of this width. It is not to be used as field bar covers.

ITEM	# 757093	ROLL
------	----------	------

MISC SINGLE PLY ACCESSORIES

MR05020 SILICONE ROLLER 1 5/16" X 1 3/4" FOR TPO

Everhard

ITEM	# 751351	ROLL
------	----------	------



MR02150 2" X 2" STEEL SEAM ROLLER FOR EPDM

Everhard

ITEM	# 751738	EACH
------	----------	------



MR08580 2" X 1/4" ROUND EDGE STEEL ROLLER for EPDM

Everhard

ITEM	# 751739	EACH
------	----------	------

ROOFING PRODUCTS

www.stetsonbuildingproducts.com



.045 REIN EPDM PERIMETER STRIP

Genflex

Composed of reinforced EPDM designed to be used as a non-penetrating wall base flashing on the Genflex EPDM membrane.

ITEM # 757085 6" X 100' ROLL
757086 9" X 100' ROLL



6" PEEL & STICK RPS W/3" TAPE GENFLEX

Genflex

GenFlex Peel and Stick RPS is composed of 6" reinforced EPDM laminated to a 3" cured EPDM based adhesive tape. GenFlex Peel and Stick RPS is designed to be used as a non penetrating wall base flashing. GenFlex Peel & Stick RPS may be used on GenFlex EPDM membrane systems.

ITEM # 757094



POURABLE SEALER A & B

Genflex

GenFlex Pitch Pan Sealer is a two part modified aromatic urethane pourable grade sealant that is used to seal around irregular penetrations on the roof. Please refer to current GenFlex specifications and details for specific application requirements.

ITEM # 757101 1 GAL. UNIT



T-JOINT COVER 8" X 10"

Genflex

GenFlex Peel & Stick T-Joint Covers are an extruded black rubber adhesive tape that is laminated to uncured EPDM rubber strips and cut to 8" (20.3cm) widths by 10" (24.5cm) lengths. GenFlex Peel & Stick T-Joint Covers are designed with an increased tape thickness in the center of the cover to flow into areas where multiple layers of cured EPDM intersect (Tjoint), forming a permanent water-tight seal on all GenFlex EPDM roofing system designs.

ITEM # 757110

Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



PEEL & STICK PIPEBOOT 1"-6" (10 BOOTS/CTN)

Genflex

GenFlex Peel and Stick Pipe Boots are specifically designed to be used in roofing applications for flashing of round penetrations. Each pipe boot will fit various penetrations and shall be cut to correct pipe diameter before installation.

ITEM # 757114

PEEL & STICK CORNERS (20/BX)

Genflex

GenFlex Peel & Stick Corners are composed of uncured EPDM laminated to a cured EPDM based adhesive tape. GenFlex Peel & Stick Corners are specifically designed to be used in roofing applications for flashing inside and outside corners. It is not to be used as T-joint covers.

ITEM # 757116

GENFLEX EPDM INSIDE CORNER (10/CTN)

Genflex

GenFlex EPDM Premolded Corners are injection molded components that make installations simple and easier than using field fabricated or field flashing procedures and details. The corners are manufactured in both inside and outside configurations. Please refer to current GenFlex EPDM specifications and details for specific applications.

ITEM # 757118



FLEXGUARD PEEL & STICK WALKWAY PAD, BLACK 30"X30"X5/16"

Genflex

Flexguard Peel & Stick Walkway Pads combine the benefits of a wear resistant rubber walkway pad with GenFlex butyl seam tape factory laminated to the bottom of the walkway pad. Combining these two high performance products makes installation to properly prepared membrane faster and easier, in addition to improving the performance of the walkway pad system. The owner is responsible for maintaining walkways in the following specific areas:

- At all access points to the roof including ladders, hatches, doorways, etc.
- Around all mechanical equipment which will require maintenance or service
- As a walkway system on roofs subjected to traffic more frequently than once a month

ITEM # 757120

ROOFING PRODUCTS

www.stetsonbuildingproducts.com



GENFLEX CLEANER

Genflex

GenFlex Cleaner is required on EPDM systems prior to applying splice adhesive or tape products. GenFlex Cleaner is to be used on GenFlex TPO membrane before splicing when contaminants prohibit a proper weld. Additionally, it is required when using GenFlex Tape products on GenFlex TPO membrane.

ITEM # 757130 5 GAL. PAIL



RM CLEANING SOLVENT **#051110**

Genflex

GenFlex Cleaning Solvent may be used on GenFlex RM Membrane before splicing when contaminants prohibit a proper weld.

ITEM # 757340 5 GAL. PAIL



RM OUTSIDE CORNER "WHITE" #061290 (10 CORNERS/BX)

Genflex

Heat-Weldable outside corner for the RM (PVC) Membrane Roof Systems.

ITEM # 757351



RM INSIDE CORNERS "WHITE" #061300 (10 CORNERS/BX)

Genflex

Heat-Weldable inside corner for the RM (PVC) Membrane Roof Systems.

ITEM # 757352



RM PIPEBOOT "WHITE" 1" TO 6" (10/BX) #061310

Genflex

GenFlex RM Premolded Pipe Boot is an injection molded components that make installations simple and easier than using existing field fabricated corners or field flashing procedures for corner type details. The boot is specifically designed to be used in roofing applications for flashing of round penetrations. The pipe boot will fit various penetrations and shall be cut to the correct pipe diameter before installations. Please refer to current GenFlex RM specifications and details for specific applications.

ITEM # 757353



TPO OUTSIDE CORNER (10/CTN)

Genflex

GenFlex TPO Premolded Corners are injection molded components that make installations simple and easier than using field fabricated or field flashing procedures and details. The corners are manufactured in both inside and outside configurations. Please refer to current GenFlex RM specifications and details for specific applications.

ITEM	# 757445	WHITE	#30018
	# 757495	GREY	#30207



TPO INSIDE CORNER (10/CTN)

Genflex

GenFlex TPO Premolded Corners are injection molded components that make installations simple and easier than using field fabricated or field flashing procedures and details. The corners are manufactured in both inside and outside configurations. Please refer to current GenFlex RM specifications and details for specific applications.

ITEM	# 757448	WHITE	#30019
	# 757498	GREY	#30208

TPO PIPEBOOTS 1" TO 6"

Genflex

GenFlex TPO Premolded Pipe Boot is an injection molded component that makes installations simple and easier than using field fabricated or field flashing procedures and details. The boot is specifically designed to be used in roofing applications for flashing of round penetrations. The pipe boot will fit various penetrations and shall be cut to the correct pipe diameter before installations. Please refer to current GenFlex TPO specifications and details for specific information.

ITEM	# 757451	WHITE	#30020
	# 757489	GREY	



TPO P.S. PIPEBOOTS 1"-6" WHITE (8/BOX)

Genflex

GenFlex White TPO Peel & Stick Pipe Boot is an injection molded TPO component with a white pressure-sensitive tape that makes installations simpler and easier than using field fabricated or field flashing procedures and details. The boot is specifically designed to be used in roofing applications for flashing of round penetrations. The pipe boot will fit various penetrations and shall be cut to the correct pipe diameter before installations. Please refer to current GenFlex TPO specifications and details for specific information.

ITEM # 757452

TPO HEAT WELDABLE WALK PAD 30" X 60' (WHITE)

Genflex

GenFlex TPO Heat Weldable Walkway Pads are to be used wherever required by GenFlex TPO specifications. They may also be used, when not specified, for the protection of the GenFlex TPO membrane at various pressure points on the roof, such as sleepers.

ITEM # 757460



TIETEX T-272 6"X180' WOVEN POLYESTER

Inland Coatings

Used with the RC2200 Inland Coating System.

ITEM # 030021



RPM-400 4"X180' POLYESTER MESH (9 RL BOX)

Inland Coatings

Inland's RPM series polyester mesh is a stitchbonded material that is ideally suited for use with Inland's RC series of synthetic rubber coatings. The parallel fiber structure allows Inland rubber coatings to quickly wetout and totally saturate. These properties ensure a true monolithic membrane, which remains intact even under thermal shock conditions.

ITEM # 030024



METAL & TILE UNDERLAYMENT 1 SQUARE ROLL 60 MILS

Tamko

TW METAL AND TILE UNDERLAYMENT is a flexible, self-adhering rubberized asphalt sheet membrane with a polymeric film on the surface and a split removable silicone-treated released sheet on the adhesive side for fast, easy installation. TAMKO TW METAL AND TILE UNDERLAYMENT is well suited for application under metal and tile roofs where prevention of water penetration is required. TW METAL AND TILE UNDERLAYMENT provides excellent waterproofing protection, withstands high temperature conditions up to 260 degrees F., and is not-abrasive to help prevent scratching of the metal during application.

Textured surface provides enhanced skid resistance — without being abrasive.

- Split plastic release film for easier installation
- Meets ASTM D1970 for nail sealability of self-adhered roofing underlayments
- High temperature resistance up to 260 degrees F.
- Can be left exposed for up to 90 days before application of metal roof or tile

ITEM # 752098

ROOFING PRODUCTS

www.stetsonbuildingproducts.com

PLY AND BASE SHEET ROLLS

TRI-FLEX 30 ROOF UNDERLAYMENT 41.5" X 300'

W.R. Grace


TRI-FLEX®30 is designed to answer the toughest roofing challenges faced by builders, architects, and specifiers.

TRI-FLEX®30 meets all national building codes and is ideal for new construction or re-roofing projects, both residential and commercial.

Stronger and lighter than felt, more cost effective than peel and stick membranes, TRI-FLEX®30 is a step above the rest. A sophisticated alternative to traditional products. From ice-cold blizzards to blazing deserts.

TRI-FLEX®30 Whether you are installing shingles, tile, slate, or metal, TRI-FLEX®30 affords you maximum protection of the building interior and assures the long-term performance of the roofing system. It maintains it's strength and will not absorb water, tear easily or degrade from exposure to the elements.

ITEM # 757600



GAF PLY 4, 5 SQ ROLL

GAF Materials

GAFGLAS Ply 4 roofing felt is constructed with a strong glass fiber mat that is coated with the finest quality asphalt, and is designed with optimum porosity to assure a sound, watertight membrane.

ITEM # 753018

75 BASE SHEET, 3 SQ

GAF Materials

GAFGLAS#75 Base Sheet is a premium roofing base sheet constructed with a strong glass mat that is coated on both sides to assure a closed-sheet design to prevent asphalt bleed-through. The sealed sheet also serves as an effective flame retarder for the application of torch-applied modified bitumen membranes.

ITEM # 753020



Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



STRATAVENT ELIMINATOR PERFORATED BASE SHEET 1 SQ ROLL

GAF Materials

GAFGLAS STRATAVENT Base Sheets are premium-grade roofing felts constructed around strong glass fiber mats and high quality asphalt. The bottom of the sheet is granule-surfaced to provide positive venting of any trapped gases under the roof membrane. STRATAVENT Base Sheets are available for nailable and nonnailable substrates. GAFGLAS STRATAVENT Nailable Base Sheet is mechanically attached to wood, structural wood fiber, poured gypsum, and lightweight insulating concrete decks. GAFGLAS STRATAVENT Perforated Base Sheet is unique in the industry: its patent pending perforated design allows mopping asphalt to flow through to the substrate as the next ply of the roof system is installed. The flow-through asphalt uniformly bonds the STRATAVENT Perforated Base Sheet and the subsequent roof system to the substrate.

ITEM # 753022



RUBEROID 20 SMOOTH 1.5 SQ ROLL

GAF Materials

Touch resilient modified bitumen membrane with a strong resilient non-woven glass mat that is coated with a flexible polymer modified asphalt.

ITEM # 753042



ICE & WATER SHIELD MB190 3' X 75'

WR Grace

Grace Ice & Water Shield® membrane is composed of two waterproofing materials—an aggressive rubberized asphalt adhesive backed by a layer of high density cross laminated polyethylene. The rubberized asphalt surface is backed with a release paper that protects its adhesive quality. During application, the release paper is removed, allowing the rubberized asphalt to bond tightly to the roof deck. The membrane is supplied in two roll sizes. Membrane strips are also available in 22.9 m (75 ft.) long rolls at widths of 150 mm (6 in.), 225 mm (9 in.), 300 mm (12 in.) and 450 mm (18 in.).

ITEM # 717474

ROOFING PRODUCTS

www.stetsonbuildingproducts.com



ICE AND WATER SHIELD VYCOR BASIK 3'X50'

WR Grace

Self-Adhered Roofing Underlayment for General Roof Leak Protection. Vycor Basik is an economical, easy-to-apply roofing underlayment suitable for - Protection from ice dams in moderate climates; protection from wind driven rain or strong storms; application as a vapor barrier; Application as a temporary roof; the rubberized asphalt adhesive is backed by a plastic split release liner that protects its adhesive quality. The release liner is easily removed during membrane application allowing the rubberized asphalt to bond to the roof deck. Vycor Basik is 1.5 mm (60 mil.) thick and is available in a 13.9 square meters (150 square feet) roll with dimensions of 914 MM (36 in.) x 15.2 m (50 ft.)

ITEM # 717476



FELT

Primesource/Metropolitan

NO. 15 & NO. 30 ASTM Saturated Felt features a premium quality organic felt (non-perforated) that is saturated with asphalt.

ITEM # 717298	15 LB ROLL	3'X144'
# 717300	30 LB ROLL	3'X66 2/3'



TAM PLY IV - 5 SQ (COVERAGE 540 SF)

Tamko

TAM-PLY IV® is a high-performance fiberglass ply sheet constructed with a TAMKO® fiberglass mat coated with weathering-grade asphalt. It has product and system tensile strength exceeding current ASTM and NBS-55 recommendations.

ITEM # 752011

Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



AWAPLAN 170 - 1 SQ 'BLACK' (COVERAGE 111.2 SF)

Tamko

AWAPLAN 170 is reinforced with a 180 g/m² nonwoven polyester mat saturated with asphalt and coated on both sides with SBS rubber modified asphalt and surfaced with ceramic granules for protection from ultraviolet degradation.

ITEM # 752026

ASPHALT BASE COATINGS

ASPHALT TYPE III STEEP 100# CARTON

Spirit Asphalt Products

Asphalt for a hot applied roofing system.

ITEM # 753000

ASPHALT TYPE IV STEEP 100# CARTON

Spirit Asphalt Products

Asphalt for a hot applied roofing system.

ITEM # 753005

GAF STANDARD ASPHALT/CONCRETE PRIMER #307

GAF Materials

A penetrating solution of select asphalt base in a petroleum solvent.

ITEM # 753052 5 GAL. PAIL



ALUMINUM COATINGS

KARNAK #97AF FIBERED ALUMINUM ROOF COATING

Karnak

Karnak #97AF Fibered Aluminum Roof Coating is made of selected asphalts and pigment flakes of pure aluminum, blended with refined solvents and mineral fibers for heavy-duty service. When Karnak #97AF Fibered Aluminum Roof Coating is applied to the roof, the aluminum flakes arrange themselves in overlapping parallel layers, forming a reflective, metallic shield over the base material.

ITEM # 756000 5 GAL. PAIL

