



AWAPLAN 170 - 1 SQ 'BLACK' (COVERAGE 111.2 SF)

Tamko

AWAPLAN 170 is reinforced with a 180 g/m² nonwoven polyester mat saturated with asphalt and coated on both sides with SBS rubber modified asphalt and surfaced with ceramic granules for protection from ultraviolet degradation.

ITEM # 752026

ASPHALT BASE COATINGS

ASPHALT TYPE III STEEP 100# CARTON

Spirit Asphalt Products

Asphalt for a hot applied roofing system.

ITEM # 753000

ASPHALT TYPE IV STEEP 100# CARTON

Spirit Asphalt Products

Asphalt for a hot applied roofing system.

ITEM # 753005

GAF STANDARD ASPHALT/CONCRETE PRIMER #307

GAF Materials

A penetrating solution of select asphalt base in a petroleum solvent.

ITEM # 753052 5 GAL. PAIL



ALUMINUM COATINGS

KARNAK #97AF FIBERED ALUMINUM ROOF COATING

Karnak

Karnak #97AF Fibered Aluminum Roof Coating is made of selected asphalts and pigment flakes of pure aluminum, blended with refined solvents and mineral fibers for heavy-duty service. When Karnak #97AF Fibered Aluminum Roof Coating is applied to the roof, the aluminum flakes arrange themselves in overlapping parallel layers, forming a reflective, metallic shield over the base material.

ITEM # 756000 5 GAL. PAIL



ROOFING PRODUCTS

www.stetsonbuildingproducts.com



FIBERED ALUMINUM COATING 3#

Tamko

Superior protective coatings made with high-quality asphalts, petroleum solvents, tough fibers and top-grade aluminum pigments. Forms a highly reflective surface upon application. Available in 1.5', 2' and 3-lb. aluminum formulations. 100% ASBESTOS FREE

ITEM # 752500 5 GAL. PAIL

ELASTOMERIC COATINGS

FLEXIBLE SEAL 10 OZ (25CS)

AC Products Inc.

Flexible Seal is a single component, paintable, elastomeric sealant primarily designed for use in the sealing of small joints or cracks (up to 1/4"). It is also used to resist water and weather elements on residential and commercial roofs. The contractor can seal damp surfaces under all types of weather conditions. It may be applied at temperatures as low as -20 degrees F.

ITEM # 755306 BLACK
755310 CLEAR
755314 GREY
755318 WHITE



RC2200 RUBBER SEAM COMP.

Inland Coatings

RC-2200 is a dense white rubber compound that is extremely effective for sealing cracks, laps, fasteners and penetrations on roof surfaces. It has the needed flexibility, tensile strength and adhesion to withstand the expansion and contraction encountered at seams, joints and penetrations. RC-2200 is also compatible with reinforcing materials such as polyester mesh.

ITEM # 030000 SPRAY GRADE WHITE 5 GAL.
030002 TROWEL GRADE WHITE 5 GAL.
030003 TROWEL GRADE WHITE 1 GAL.
030004 BRUSH GRADE WHITE 5 GAL.
030005 BRUSH GRADE WHITE 1 GAL.

Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572



RC2000 ROOF COATING

Inland Coatings

Inland Rubber Roof Coating provides a cost effective solution for many of today's roofing problems. RC-2000's added protection reduces costly patching and expensive re-applications. Inland Rubber Roof Coating has high resistance to acids, alkali and salts. It is thermally stable and is unaffected by temperature changes; exhibits excellent abrasion resistance and superb adhesion to a wide variety of surfaces.

ITEM	# 030006	BEIGE	5 GAL.
	# 030011	BEIGE	1 GAL.
	# 030007	WHITE	5 GAL.
	# 030010	WHITE	1 GAL.
	# 030012	GRAY	5 GAL.
	# 030013	GRAY	1 GAL.



Technical Roofing Solutions, Inc.

1.8# FOAM, WINTER ELASTOSPRAY RT-1812

Technical Roofing Solutions, Inc.

A two component HCFC blown polyurethane spray foam system.

ITEM	# 753232	55 GAL. DRUM
------	----------	--------------

RT1812XW ARCTIC FOAM

Technical Roofing Solutions, Inc.

A two component HCFC blown polyurethane spray foam system.

ITEM	# 753234	55 GAL. DRUM
------	----------	--------------

SPECIALTY COATINGS & ADHESIVES

208 11OZ TUBE HENRY WET PATCH

Henry Sealants Division



HE208 - WET PATCH™ ROOF CEMENT is a premium asphalt-containing compound for sealing roof leaks on wet surfaces. It patches holes and cracks even in a driving rain or under water, and is so versatile it may be used whether the weather is wet or dry, hot or cold. Especially easy to spread in cold temperature, HE208 - WET PATCH™ ROOF CEMENT is made from heavy-bodied refined asphalt, organic fibers, petroleum solvent, and a water displacement agent. Meets or exceeds all requirements of ASTM Specification D-4586, Type I and 100% wet surface adhesion as per ASTM D-3409.

ITEM	# 754060
------	----------

Omaha, NE (800) 383-1272 • Rockford, IL (800) 383-3808
Rock Island, IL (800) 383-1240 • Waterloo, IA (800) 383-2959