

THERMAL/WATERPROOFING/ DOORS

www.stetsonbuildingproducts.com

WATERPROOFING/DAMPROOFING/VAPOR BARRIERS

FLUID WATERPROOFING

HLM 5000

Degussa Building Systems



Liquid cold-applied elastomeric waterproofing membrane system; Features: standard and high-build systems; waterproofs concrete; elastomeric; wide service temperature range; chemical resistant; seamless cold-applied membrane; asphalt-modified polyurethane; may be applied to green concrete with appropriate primer.

ITEM	# 713133	TROWEL GRADE	5 GAL PAIL
	# 713134	SELF LEVELING	5 GAL PAIL
	# 713135	SPRAY GRADE	5 GAL PAIL
	# 713140	ROLLER GRADE	5 GAL PAIL

MEL-ROL LM

W.R. Meadows



MEL-ROL LM is a single component, polymer-modified, cold-applied, liquid waterproofing membrane ideal for both above and below grade vertical waterproofing applications. This heavy-bodied, liquid membrane is ideal for immediate application to newly stripped, below grade concrete walls and for use with insulated concrete forms (ICF's).

ITEM	# 717006	5 GAL PAIL
------	----------	------------



TREMPROOF 60/201

Tremco

TREMProof 60 is a single-component, bitumen-modified, moisture curing polyurethane waterproofing membrane. TREMProof 60 is available in three viscosities (H, V and R) suitable for applications to horizontal and vertical surfaces.

ITEM # 712111 5 GAL PAIL

Tremproof 201 is a high solids, VOC compliant, modified polyurethane waterproofing membranes. Tremproof 201 is a one-part moisture curing elastomer. Tremproof 201 is formulated from the same high quality polymer; are available in four viscosities (L, H, R, and T) that are suitable for applications to horizontal and vertical surfaces.

ITEM # 794072	TROWEL GRADE	5 GAL PAIL
# 794105	VERTICAL GRADE	5 GAL PAIL
# 794108	HORIZONTAL GRADE	5 GAL PAIL
# 794109	ROLLER GRADE	5 GAL PAIL



TREMPROOF 250GC

Tremco

Tremproof 250 GC is a fluid-applied, elastomeric waterproofing membrane that can be applied to "Green" Concrete. Tremproof 250 GC is an aliphatic, rapid curing, high solids, VOC compliant, modified polyurethane waterproofing membrane that can be applied to Green Concrete. Tremproof 250 GC is a one-part moisture curing elastomer that is suitable for applications to horizontal and vertical surfaces.

ITEM # 794102 5 GAL PAIL

FLUID DAMPPROOFING

HYDROCID

Degussa Building Systems



Waterborne emulsified-asphalt dampproofing compounds; Features: suitable for "green" or slightly damp surfaces; nonflammable; uncured material may be cleaned with water; flexible; -40 degrees to 150 degrees Fahrenheit (-40 degrees to 60 degrees Celsius) service temperature range. -40 to 150° F (-40 to 66° C) Hydrocide® 600 is fiber-free for application by brush or spray. Hydrocide® 700 is reinforced with long fibers for application by trowel. Hydrocide® 700B is reinforced with short fibers for application by brush or spray.

ITEM # 713015	600 (FIBER FREE)	5 GAL PAIL
# 713020	600 (FIBER FREE)	55 GAL DRUM
# 713025	700 (LONG FIBER REINFORCED)	5 GAL PAIL
# 713035	700B (SHORT FIBER REINFORCED)	5 GAL PAIL
# 713036	700B (SHORT FIBER REINFORCED)	55 GAL DRUM

THERMAL/WATERPROOFING/ DOORS

www.stetsonbuildingproducts.com



HYDROCIDE MASTICS

Degussa Building Systems

Below-grade and cavity-wall solvent-based asphalt dampproofings; Features: continuous film without cracks or pinholes; adheres to concrete, masonry, and steel; -40 degrees Fahrenheit to 150 degrees Fahrenheit (-40 degrees to 66 degrees Celsius) service temperature range; elastic properties; quick drying; VOC compliant, asbestos free. Mastic contains long fibers for trowel application. Semi-Mastic contains short fibers for brush or spray application. 128 Spray Mastic contains selected fibers for spray application (or trowel at low temperatures). 648 Mastic is fiber-free for application by brush or spray.

ITEM # 713030	128 SPRAY MASTIC	55 GAL DRUM
# 713040	648 MASTIC (FIBER FREE)	5 GAL PAIL
# 713045	MASTIC (LONG FIBERS)	5 GAL PAIL
# 713050	SEMI-MASTIC (SHORT FIBERS)	5 GAL PAIL

BENTONITE WATERPROOFING

BENTONITE

A premium, Wyoming type, high swelling, granular, sodium bentonite. When in the presence of water, Bentonite reacts and forms an impervious waterproof gel. Granular product.


ITEM # 719000	100 LB. BAGS.
---------------	---------------

PARASEAL WATERPROOFING

Tremco

Paraseal is a sheet waterproofing membrane manufactured to controlled thickness of 150 mils to 200 mils of tough, high density polyurethane (HDPE) and expandable, quality granular Bentonite. The Bentonite, capable of expanding to 6 times its thickness, is laminated at a rate of up to one pound per square foot to the impermeable HDPE sheet forming a superior Dual Waterproofing System for application to horizontal and vertical surfaces.

ITEM # 794369	4'X24' ROLL 15 MILS THICK
---------------	---------------------------



Cedar Rapids, IA (800) 383-7272 • Des Moines, IA (800) 383-2181
Dubuque, IA (800) 894-6272 • Grand Island, NE (800) 228-8572